

Baltic logo Print

Technical Datasheet



Product:	Jet-Print	Standard widths with borders: 60 cm, 75 cm, 85 cm, 115 cm, 150 cm and 200 cm
Customs tariff number:	57032098	Standard widths 3 cm smaller than for mats with borders without borders: (e.g. 57 cm)
Product details:	<div>» Custom designs</div> <div>» Stops dirt and moisture</div> <div>» Durable nylon surface</div> <div>» Special colours going by Pantone, HKS or RAL possible for a surcharge</div> <div>» Special shapes possible</div> <div>» Skid resistant rubber back</div> <div>» PVC-free</div> <div>» Suitable for underfloor heating</div> <div>» 5 year Manufacturers Guarantee*</div> <div>» Made in Europe</div>	<div>Standard lengths: all lengths up to 400 cm</div> <div>Bespoke lengths: up to 700 cm</div> <div>Colouration: Chromojet printing process</div> <div>Pile: 100 % High-Twist Nylon (HTN) Polyamide 6.6 Pile height: approx. 8 mm</div> <div>Pile weight: without substrate: 680 g/sqm with substrate: 780 g/sqm</div> <div>Backing: 100 % Nitrile rubber</div> <div>Available with kleeled or smooth backing</div> <div>Rubber thickness: 1.40 mm</div> <div>Rubber weight: 1.70 kg/sqm</div> <div>Border width: 20 mm</div> <div>Available with or without borders</div> <div>Border thickness: 2.40 mm</div> <div>Cleaning: » Washable up to 60 °C (Washing is not recommended for mats without borders when rubber backing is less less than 1.8 mm thick)</div> <div>» Tumble dry up to 60 °C</div>
Burning behaviour:	EN 13501-1 / Cfl-s1	
Static electrical propensity:	EN 14041 Antistatic	
Slip resistance:	NFSI High-Traction	
Total mat weight:	2.48 kg/sqm	
Overall height:	approx. 9 mm	
Dirt absorption:	600 g/sqm	
Moisture absorption:	3 - 4 l/sqm	
Application areas:	<div>» Indoor placement</div> <div>» Entrances</div> <div>» Corporate identity</div> <div>» Point of Sale</div> <div>» Any marketing message</div>	
Colours:		

